

4-2015

Context-Driven Automatic Subgraph Creation for Literature-Based Discovery

Delroy H. Cameron

Wright State University - Main Campus, cameron.20@wright.edu

Ramakanth Kavuluru

Wright State University - Main Campus

Thomas Rindflesch

Amit P. Sheth

Wright State University - Main Campus, amit@sc.edu

Krishnaprasad Thirunarayan

Wright State University - Main Campus, t.k.prasad@wright.edu

See next page for additional authors

Follow this and additional works at: <https://corescholar.libraries.wright.edu/knoesis>



Part of the [Bioinformatics Commons](#), [Communication Technology and New Media Commons](#), [Databases and Information Systems Commons](#), [OS and Networks Commons](#), and the [Science and Technology Studies Commons](#)

Repository Citation

Cameron, D. H., Kavuluru, R., Rindflesch, T., Sheth, A. P., Thirunarayan, K., & Bodenreider, O. (2015). Context-Driven Automatic Subgraph Creation for Literature-Based Discovery. *Journal of Biomedical Informatics*, 54, 141-157.
<https://corescholar.libraries.wright.edu/knoesis/851>

This Article is brought to you for free and open access by the The Ohio Center of Excellence in Knowledge-Enabled Computing (Kno.e.sis) at CORE Scholar. It has been accepted for inclusion in Kno.e.sis Publications by an authorized administrator of CORE Scholar. For more information, please contact library-corescholar@wright.edu.

Authors

Delroy H. Cameron, Ramakanth Kavuluru, Thomas Rindflesch, Amit P. Sheth, Krishnaprasad Thirunarayan, and Olivier Bodenreider

Context-Driven Automatic Subgraph Creation for Literature-Based Discovery

Delroy Cameron^{a,*}, Ramakanth Kavuluru^b, Thomas C. Rindflesch^c, Amit P. Sheth^a, Krishnaprasad Thirunarayan^a, Olivier Bodenreider^c

^aOhio Center of Excellence in Knowledge-enabled Computing (Kno.e.sis)
Wright State University, Dayton OH 45435, USA

^bDivision of Biomedical Informatics, University of Kentucky, Lexington, KY 40506, USA

^cNational Library of Medicine, 8600 Rockville Pike, Bethesda MD 20894, USA

Abstract

Background: Literature-based discovery (LBD) is characterized by uncovering hidden associations in non-interacting scientific literature. Prior approaches to LBD include use of: 1) domain expertise and structured background knowledge to manually filter and explore the literature, 2) distributional statistics and graph-theoretic measures to rank interesting connections and 3) heuristics to help eliminate spurious connections. However, manual approaches to LBD are not scalable and purely distributional approaches may not be sufficient to obtain insights into the meaning of poorly understood associations. While several graph-based approaches have the potential to elucidate associations, their effectiveness has not been fully demonstrated. A considerable degree of *a priori* knowledge, heuristics and manual filtering is still required.

Objectives: In this paper we implement and evaluate a context-driven, automatic subgraph creation method that captures multifaceted complex associations between biomedical concepts for LBD. Given a pair of concepts, our method automatically generates a ranked list of subgraphs, which provide informative and potentially unknown associations between such concepts.

Methods: To generate subgraphs, the set of all MEDLINE articles that contain either of two specified concepts (A, C) are first collected. Binary relationships or assertions, which are automatically extracted from the MEDLINE articles, called *semantic predications*, are then used to create a labeled directed *predications graph*. In this graph, a *path* is represented as a sequence of semantic predications. The hierarchical agglomerative clustering (HAC) algorithm is then applied to cluster paths, which are bounded by the two concepts (A, C) based on the definition of the *context* of a path, as a set of Medical Subject Heading (MeSH) descriptors. Paths that exceed a threshold of semantic relatedness are clustered into subgraphs based on their *shared context*. The automatically generated clusters are then provided as a ranked list of subgraphs.

Results: The subgraphs generated using this approach facilitated the rediscovery of 8 out of 9 existing scientific discoveries. In particular, they directly (or indirectly) led to the recovery of several *intermediates* (or B-concepts) between A and C, while also providing insights into the meaning of each association. Such meaning is derived from predicates between the concepts, as well as the provenance of the semantic predications in MEDLINE. Additionally, by generating subgraphs on different thematic dimensions (such as *Cellular Activity*, *Pharmaceutical Treatment* and *Tissue Function*), the approach enables a broader understanding of the nature of complex associations between concepts in a domain. In a statistical evaluation to determine the *interestingness* of the subgraphs, it was observed that an arbitrary association is mentioned in only approximately 4 articles in MEDLINE on average.

Conclusion: These results suggest that leveraging the implicit and explicit context provided by manually assigned MeSH descriptors is an effective representation for capturing the underlying semantics of complex associations, along multiple thematic dimensions for LBD.

Keywords: Literature-based discovery (LBD), Graph mining, Path clustering, Hierarchical agglomerative clustering, Semantic Similarity, Semantic relatedness, Medical Subject Headings (MeSH)

1. Introduction

Leveraging rich representations of textual content from scientific literature could be effective for finding and elucidating

complex associations. Rich representations exploit implicit, formal (or explicit) and powerful semantics [1] to capture context, which may be important in providing deeper insights into the nature of associations. Gordon and Dumais made this crucial observation in [2] after successfully applying the popular technique of Latent Semantic Indexing (LSI) for LBD. The authors reported that LSI was only slightly more effective than

*Corresponding Author. Tel.: +1 937 775 5213; fax: +1 937 775 5133
Email address: delroy@knoesis.org (Delroy Cameron)

traditional frequency-based metrics, such as token frequency, record frequency and term frequency-inverse global frequency (*tf-igf*) [3] for finding intermediates. While LSI was successful for knowledge rediscovery, the authors speculated that richer representations of textual content are needed to capture “*evidence suggestive of ‘causal’ relationships in the literature (which may be revealed independently of their statistical prominence).*” Moreover, they stressed the need for “*semantic and category knowledge to improve the step of identifying [intermediate and] terminal concepts.*”

Many techniques for finding hidden connections (or associations) between biomedical concepts from scientific literature however, utilize frequency-based and graph-theoretic metrics. Few methods have been developed to seamlessly find and elucidate complex associations, by going beyond reliance on implicit semantics. The conventional wisdom has been that discoveries are likely to arise from logical connections between source (A) concepts, intermediates (B) and targets (C) that **frequently or rarely (co) occur** in the literature, or are **highly or rarely** connected in a knowledge base. The earliest frequency-based approaches utilized ‘frequency of occurrence’ mainly through measures of term (and concept) frequency [4, 5]. Other measures such as relative frequency, token frequency, term frequency-inverse global frequency (*tf-igf*) [3] and term frequency-inverse document frequency (*tf-idf*) [6, 7] were also used to rank intermediates. Subsequent approaches utilized ‘frequency of co-occurrence’ using techniques such as LSI [2], association rules [8, 9, 10, 11] and probability distributions [11, 12, 13, 14]. Torvik et. al. [12, 15] even used an ensemble approach to find intermediates that combined statistical and temporal features.

While distributional approaches have been used for LBD, a critical issue is the realization that the underlying frequencies only provide an indirect way of capturing the meaning of associations. For instance, consider the association in which *Dietary Fish Oils* (A) inhibit *Platelet Aggregation* (B) and the aggregation of blood platelets causes *Raynaud Disease* (C); a circulatory disorder that causes periods of severely restricted blood flow to the fingers and toes [38]. While *Dietary Fish Oils*, *Platelet Aggregation*, and *Raynaud Disease* may frequently co-occur in the literature, their precise association is not explicitly captured by their co-occurrence. A second issue is that the underlying frequency distribution may not be adequate for capturing related concepts, which may be important in elucidating causal relationships and mechanisms of interaction.

To address these problems, several relations-based techniques [16, 17, 18] have been developed, which use the explicit relationships (or predicates) between concepts. Such predicates are typically obtained from structured background knowledge or known *a priori* by domain experts. For example, Hristovski et. al. in [17], developed a relations-based approach that used ordered alternating sequences of predicates and classes (or semantic types) called *discovery patterns*. These patterns are also specified *a priori* using insights from background knowledge. Using discovery patterns, Hristovski argues that if a *Disease* causes a change in a *Substance/Body Function* and a *Drug* inhibits this change, then the *Drug* MAYBE_TREATS the *Disease*.

The *CAUSES-INHIBITS* sequence is used to uncover potentially new *Drug* treatments for the *Disease*.

While intuitive, the relations-based approach is mainly applicable in scenarios where both predicates and semantic types are known, or can be easily obtained. This is not always trivial. For example, consider the complex scenario depicted in Figure 1, in which *Dietary Fish Oils* produce several *Prostaglandins*, including *Prostaglandin I3 (PGI3)* and *Epoprostenol (PGI2 also called Prostacyclin)*. The latter of these *Prostaglandins* (*Epoprostenol*) treats *Raynaud Syndrome* and also disrupts *Platelet Aggregation*. Since *Platelet Aggregation* causes *Raynaud Syndrome* one can reasonably conclude that a plausible mechanism by which *Dietary Fish Oils* treat *Raynaud Syndrome* is through the production of *Prostaglandins*, which actively disrupt *Platelet Aggregation*, deemed a cause of *Raynaud Syndrome*. Obviously such complex situations, involving several predicates and disparate concepts may be unknown initially by domain experts. The relations-based approach is therefore considered unsuitable for complex associations.




Figure 1: Complex association between Dietary Fish Oils and Raynaud Syndrome

It can be argued that hierarchical relations from the schema of a domain specific knowledge base, such as the Unified Medical Language System (UMLS) can also be used to create such complex subgraphs, using measures like specificity. However, the semantic types for *Prostaglandins* and *Platelet Aggregation* are *Eicosanoids* and *Cell Function*, respectively. These semantic types share no common ancestors in their lineage in the UMLS Semantic Network¹. And while associative relations can be used instead, a proven and repeatable schema-driven approach that captures this level of complexity has not been forthcoming.

Instead, contemporary approaches to LBD focus on creating subgraphs, which comprise of binary relations, called *semantic predications*, of the form (subject, predicate, object). These predications are extracted directly from assertions in scientific literature. Wilkowski et. al. [19] developed a graph-theoretic approach based on semantic predications that iteratively (and manually) uses a greedy strategy to create the best subgraph,

¹There are three semantic types for Prostaglandins (i.e., Eicosanoid, Pharmacologic Substance, and Biologically Active Substance) and one semantic type for Platelet Aggregation (i.e., Cell Function) in the UMLS. These semantic types do not overlap in the UMLS Semantic Network hierarchy – <https://uts.nlm.nih.gov/semanticnetwork.html>




Figure 2: Thematic dimensions of association for Raynaud Syndrome and Dietary Fish Oil

by weighting edges using degree centrality. This approach was used to elucidate the association among *Norepinephrine*, *Depression*, and *Sleep*.

Wilkowski’s approach bears semblance to the approach by Ramakrishnan et. al. [20], in which a greedy strategy is applied, using an ensemble of features, to generate complex associations. While the approach is fully automatic, it uses class and property specificity, instance-level rarity and refraction, applied to statements in a synthetically generated dataset, instead of semantic predications. Ramakrishnan notes that this approach was used, in exploratory research, to recover the connections from the *Raynaud Syndrome – Dietary Fish Oils* discovery. However its broader applicability for LBD in general has not been fully demonstrated. Reliance on hierarchical relationships in the UMLS Semantic Network is subject to inconsistencies since the UMLS is a terminology and not a formal ontology. Also, by design, the trees in the UMLS Semantic Network are fairly disjoint, as for *Prostaglandins* and *Platelet Aggregation*.

Goodwin et. al. [21] developed a hybrid approach that uses spreading activation for LBD, deriving weights from relative frequencies (of concepts and semantic predications) and degree centrality. This approach was used to successfully recover the intermediate *Cortisol* in the *Testosterone – Sleep* discovery [22], and also to elucidate the *Norepinephrine*, *Depression*, and *Sleep* scenario from [19]. However, Goodwin generates a list of intermediates, instead of a graph. It is unclear how the spreading activation algorithm might be adapted to capture the context of complex associations. In [23] van der Eijk et. al. clustered only MeSH² descriptors (not semantic predications) into subgraphs, based on frequency of co-occurrence and Hebbian Learning. This approach provided new insights into the association between *Deafness* and *Macular Dystrophy*, and between *Insulin* and *Ferritin*. In recent work, Spangler et. al. [24] also used distributional statistics (tf-idf) to weight edges in a kinase network, represented as a Laplacian Matrix. The approach creates an *n*-ary similarity tree in which 7 new *p53* kinases were discovered, which could revolutionize *Cancer* treatments.

In spite of the successes of graph-based and frequency-based approaches for LBD, more effective methods for capturing the context of associations are desired. Gordon and Dumais suggested a possible independence between frequency and causality for LBD in [2]. We believe that complex associations that elucidate the relationships among concepts depend both on implicit and explicit context. Further, we believe that capturing

such context may be the important in segregating complex associations along multiple thematic dimensions. For example, Figure 2 shows that *Dietary Fish Oils* and *Raynaud Syndrome* are associated in at least the following three ways: 1) in terms of *Cellular Activity* involving *Blood platelets/Prostaglandins*, as shown in Figure 2a, 2) through *Pharmaceuticals* such as *Nifedipine* and *Verapamil*, as shown in Figure 2b and 3) through *Lipids/Fatty Acids* from *Efamol* and *Evening primrose oil*, as shown in Figure 2c.

The approach for clustering of cliques developed by Zhang et. al. [25, 26] may be used to capture subgraphs on multiple thematic dimensions. However, the approach is based on degree centrality and is therefore more likely to create subgraphs that only consist of highly connected concepts from the literature. In this paper, we explore the idea that **hidden connections, and their related concepts, which help elucidate underlying complex associations, are more dependent on context than frequency, connectivity or specificity.**

This research builds on our previous approach in [27] in which we rediscovered and decomposed the *Raynaud Syndrome – Dietary Fish Oils* discovery by using domain expertise, as context to manually create the subgraphs. Here, we present a method to automatically create the subgraphs by gleaning implicit and explicit context using MeSH descriptors. To achieve this, we first specify the context of a semantic predication and then use it to infer the context of a path. Such paths are then clustered into coherent subgraphs on multiple thematic dimensions, based on their shared context.

The approach requires only three items from the user as input: 1) a list of concept labels for source (A) and target (C), 2) the maximum path length *k* of paths to be generated (default *k* = 2, for ABC associations) and 3) a cut-off date *dt* for articles to be included from the scientific literature. If no cut-off date is provided all MEDLINE articles are used. The output of the approach is a ranked list of subgraphs *S*.

To facilitate understanding the meaning of associations present in the subgraphs, the predicates of the semantic predications and their provenance in MEDLINE are provided (see Section 3). Relationships that are not explicit in the subgraphs, but are inferred, can be explored by composing MEDLINE queries (as we will show). The collective use of predicates, provenance and MEDLINE queries for knowledge exploration constitute the notion of *discovery browsing*³, introduced by Wilkowski [19] and extended by Cairelli [28].

²Medical Subject Headings (MeSH) – <https://www.nlm.nih.gov/mesh/>

³Discovery browsing is enabled when a system guides the user through their

To assess the efficacy of our approach, two forms of evaluation were conducted. An evidence-based evaluation showed that the generated subgraphs could facilitate the rediscovery of 8 out of 9 existing discoveries [29, 30, 31, 32, 33, 34, 22, 28]. A statistical evaluation to determine the *interestingness* of the subgraphs (discussed in Section 3.2) showed that an arbitrary association occurs only in approximately 4 articles in MEDLINE on average. This suggests that the subgraphs created using our approach provide an effective way of finding and elucidating poorly understood associations. In this paper we make the following specific contributions:

1. We develop a novel context-driven subgraph creation method for closed LBD, capable of finding complex associations. Our approach is distinct from previous approaches, which are mainly based on statistical frequency, graph metrics and specificity.
2. We implement an unsupervised clustering algorithm to automatically create complex subgraphs using implicit and explicit context, without the need for complex heuristics for filtering.
3. We illustrate the role of discovery browsing, through the use of predicates and provenance to supplement the subgraphs with insights from the scientific literature.
4. We show the effectiveness of this approach in facilitating the rediscovery of 8 out of 9 existing scientific discoveries.

The rest of this paper is organized as follows: The approach to automatic subgraph creation is discussed in Section 2. Experimental Results are presented in Section 3 and a thorough discussion on limitations and future work are presented in Section 4. Conclusions are presented in Section 5.

2. Automatic Subgraph Creation

To automatically create complex subgraphs our approach relies on three datasets. The first dataset is MEDLINE, which is a repository of more than 23 million bibliographic citations maintained by the National Library of Medicine (NLM). The second is SemMedDB [35], a database of more than 65 million semantic predications extracted from MEDLINE using SemRep⁴. The third is the Biomedical Knowledge Repository (BKR), a knowledge base consisting of statements from the UMLS Metathesaurus together with semantic predications extracted using SemRep. These components are used for automatic subgraph creation in five steps: 1) Query Specification, 2) Candidate Graph Generation, 3) Path Context Representation, 4) Path Clustering and 5) Subgraph Ranking. Each step is discussed in the following subsections:

exploration of the literature in a process of cooperative reciprocity. The “*user iteratively focuses system output, thus controlling the large number of relationships often generated in literature-based discovery systems.*”

⁴SemRep – <http://semrep.nlm.nih.gov/>




Figure 3: System Architecture

2.1. Query Specification

The system (called *Obvio*⁵) first requires a query, denoted q , which can be specified initially by providing the labels of two concepts of interest (A, C). These terms are manually mapped to concept unique identifiers (or CUIs), using the UMLS Semantic Navigator⁶. For example, the A-term *Dietary Fish Oil*, maps to the UMLS concept *C0016157*, whose label is also *Fish Oils*. Initial A- and C-terms are also manually augmented with other closely related concepts. For example, the concepts *Fish oil – dietary (C0016157)* and *Eicosapentaenoic Acid (C0000545)* are closely related to *Fish Oils (C0016157)* and are therefore added to the query. Next, the cut-off date dt for the literature to be included may be optionally provided. If no cut-off date is given the system uses the entire MEDLINE database. The maximum path length k , of paths to be generated between A and C may then also be optionally provided. If none is given, the system defaults to a maximum path length of $k = 2$. An example query for *Raynaud Syndrome – Dietary Fish Oils* could be $q = (\{Fish\ Oils, Fish\ oil - dietary, Eicosapentaenoic\ Acid\}, \{Raynaud\ Phenomenon, Raynaud\ Disease\}, 11/01/1985, 3)$.

2.2. Candidate Graph Generation

Given this query $q = (A, C, dt, k)$, the *Query Processor* (Figure 3, top left) then retrieves the set of MEDLINE documents D that contain any of the terms (i.e., labels) in the A- and C- sets. These documents form the corpus from which semantic predications will be obtained. To obtain the predications, the set of PubMed identifiers (or PMIDs) for each article in D is passed to the *Predications Graph Builder*, which creates a labeled directed graph, called a *predications graph* denoted G . To achieve this, the graph builder collects the semantic predications for each document in D that are also present in SemMedDB. The builder then creates a graph in which nodes are UMLS concepts

⁵Obvio video demo - <http://bit.ly/obviodemo>, Obvio Project page - <http://wiki.knoesis.org/index.php/Obvio>

⁶Semantic Navigator – <http://mor2.nlm.nih.gov:8000/perl/auth/semnav.pl>

and edges are UMLS predicates. This graph is delivered as input to the *Subgraph Generator*, which first uses the *Path Generator* to extract all paths between (A, C) up to length k , using the Depth First Search (DFS) algorithm. DFS is selected because both A and C are known. However, the choice of Breadth First Search (BFS) may be equally effective for graph traversal, but has not been explored, since performance is not the primary focus. The path generator therefore uses the predications graph to produce paths (or ρ -path associations), where edges are oriented in either direction, consistent with our definition in [27]. This restricted set of paths is called the reachability relation R [36] (or *candidate graph*) between A and C at length k and date range dt . This candidate graph represents a more likely set from which discoveries may arise.

2.3. Path Context Representation

The candidate graph is then provided as input to the *Path Clustering Module*, which requires a definition for the context of a path p to cluster related paths into subgraphs. To specify path context, denoted $C(p)$, we first specify the context of a semantic predication t , denoted $c(t)$. The context of each predication in the path is then aggregated to obtain overall path context.

To define the context of a semantic predication, we make two assumptions, based on observations about MEDLINE articles. The first observation is that MeSH descriptors are manually assigned to MEDLINE articles (titles and abstract only) by MeSH indexers, based on human interpretation of the meaning of the entire article. These descriptors provide a *concept-level semantic summary* of the full text. Similarly, semantic predications also provide a semantic summary of the meaning of the content. However, semantic predications provide a *relational semantic summary*, by linking concepts using explicit predicates.

We therefore assume that the MeSH descriptors of an article capture its implicit context, which is shared by the semantic predications. A semantic predication can then be represented in terms of the MeSH descriptors of the article in which the predication occurs. This is the basis for our **interchangeability assumption** for subgraph creation, which states that *the concept-level semantic summary and relational semantic summary of a MEDLINE article, are interchangeable*. More specifically, given a semantic predication t and a MEDLINE article d such that t is extracted from d , the context of the semantic predication $c(t) = M(d)$, where $M(d)$ is the set of MeSH descriptors assigned to d .

If this assumption holds, then we can make a second assumption, which is that the overall context of a semantic predication t across the entire corpus can be represented as a vector of MeSH descriptors aggregated from each document containing t (based on distributional semantics). This is the basis for our **context distribution assumption** for subgraph creation, which states that *the context of a semantic predication can be expressed as the distribution of all MeSH descriptors associated with all articles that contain the predication*.

Since our fundamental premise for subgraph creation is that relatedness among concepts is independent of statistical frequency, graph metrics or specificity, our vector representation is downgraded to the Boolean-valued set representation, in which

a MeSH descriptor is either present or absent in the distribution. The context of a path

$$C(p) = \bigcup_{t \in p} c(t) \quad (1)$$

is therefore the aggregation of its predication context sets.

2.4. Path Clustering

The *Path Clustering Module* uses the *context set* $C(p)$ for each path p in the candidate graph R to cluster related paths p_i and p_j , based on their shared context. To compute this shared context between paths, the system initially computes the intersection $s''(p_i, p_j) = C(p_i) \cap C(p_j)$ of their shared MeSH descriptors. However, to account for inexact matches between MeSH descriptors across the two sets, this intersection is enhanced using the MeSH hierarchy, which provides explicit (or formal) semantics. Specifically, we use the Cartesian product of the two context sets $C(p_i) \times C(p_j)$ to determine which pairs of MeSH descriptors adequately indicate relatedness between the paths. Pairs of descriptors (m_i, m_j) , whose similarity is above some threshold of MeSH semantic similarity are retained, while those below are discarded. The key idea is to maximize the weights of the *in-context* descriptors and minimize the weights of the *out-of-context* descriptors.

To compute semantic similarity between MeSH descriptors the measure of dice similarity is used. Dice similarity computes the proportion of common ancestors between descriptors in the MeSH hierarchy (MH). For two MeSH terms m_i and m_j the dice similarity is computed as

$$dice(m_i, m_j) = 2 \times \frac{|ancestors(m_i)_{MH} \cap ancestors(m_j)_{MH}|}{|ancestors(m_i)_{MH}| + |ancestors(m_j)_{MH}|}, \quad (2)$$

where $ancestors(m_i)_{MH}$ is the set of all ancestors of m_i in MeSH. The maximum similarity between two descriptors computed using dice similarity is 1. This occurs when the descriptors are equal. (i.e., $m_i = m_j$). The range of similarity values is therefore $[0, 1]$.

In this computation, pairs of descriptors, whose dice similarity exceed the threshold of semantic similarity ($\tau_{sim} = 0.75$) are normalized to a value of 1. This normalized dice similarity

$$dice_N(m_i, m_j) = \begin{cases} 1 & \text{if } dice(m_i, m_j) > \tau_{sim} \\ 0 & \text{otherwise} \end{cases} \quad (3)$$

is therefore computed conditionally. The initial overall semantic relatedness

$$sr''(p_i, p_j) = \sum_{(a,b) \in C(p_i) \times C(p_j)} dice_N(a, b) \quad (4)$$

between p_i and p_j is the sum of the normalized pairwise dice similarity scores that exceed the threshold of semantic similarity, across the context sets $C(p_i) \times C(p_j)$.

A consequence of this *semantics-enhanced shared context*, is that a broad range of relatedness scores may exist. Paths that are very similar, which have many exact (and inexact) MeSH

descriptors in common will have very scores, while others may have low scores. To dampen the major differences in similarity scores of different path pairs, we apply a log reduction on the normalized dice similarity scores. This is achieved by first computing the relatedness score between a given MeSH descriptor a in context set $C(p_i)$ against the entire set of descriptors in the context set $C(p_j)$. This computation yields the similarity score

$$sim'(a, C(p_j)) = \sum_{b \in C(p_j)} dice_N(a, b). \quad (5)$$

The log reduction

$$sr''_L(p_i, p_j) = \sum_{a \in C(p_i)} \log(1 + sim'(a, C(p_j))) \quad (6)$$

is then applied to $sim'(a, C(p_j))$, and the overall semantic relatedness $sr''(p_i, p_j)$ between the two paths is the aggregate of the log-reduced scores for each descriptor in $C(p_i)$ and the entire set in $C(p_j)$. This metric is the basis for finding and elucidating complex associations among concepts, along multiple thematic dimensions, based on implicit and explicit context, alluded to by Gordon and Dumais in [2].

In the next step the hierarchical agglomerative clustering (HAC) algorithm is used to create subgraphs by clustering related paths. In the bucket population step, the algorithm initializes $|R|$ buckets, one for each path in the candidate graph. For a given path, the relatedness score is computed for each of the remaining $|R| - 1$ paths. If two paths are sufficiently related, they must be placed in the same cluster. To achieve this, a method to automatically determine the **threshold for path relatedness** denoted τ_{rel} , is required.

To obtain the threshold for path relatedness the distribution of path relatedness scores between all pairs of paths in the candidate graph is pre-computed (i.e., $(|R| \times |R| - 1)/2$ scores). Figure 4 shows the distribution of relatedness scores for three experiments in the initial stages of our research. Each distribution approximates to a Gaussian (or normal) distribution.

Table 1: Threshold Comparisons

Scenario	Path Relatedness Scores			Max
	2 Std. Dev	Manual	3 Std. Dev.	
Raynaud-Fish Oil	2.68	3.0	3.04	3.38
Testosterone-Sleep	3.35	3.5	3.83	6.22
DEHP-Sepsis	3.94	4.0	4.53	4.84

In statistics, the first standard deviation ($-\sigma, +\sigma$) from the mean of a Gaussian distribution corresponds to the point of inflection. This point likely indicates a shift in a trend or phenomenon. When the manually determined thresholds for path relatedness for the same three experiments were compared to the $\sigma, 2\sigma$ and 3σ of the Gaussian distribution, it was observed that the manual thresholds were consistently between the 2σ and 3σ , as shown in Table 1. The second deviation from the mean of the Gaussian distribution ($\tau_{rel} = 2\sigma$) was therefore selected as the path relatedness threshold for clustering. During clustering, all pairs of paths with relatedness scores above

this automatically determined threshold were added to the same cluster.

In the next phase of HAC (bucket merging), buckets that contain multiple paths are merged if their *inter-cluster similarity* exceeds the threshold for path relatedness. That is, for each pair of paths (p_i, p_j) across a pair of buckets B_a and B_b , the inter-cluster similarity

$$sim_{inter}(B_a, B_b) = \frac{\sum_{(p_i, p_j) \in B_a \times B_b} sr''_L(p_i, p_j)}{|B_a| \cdot |B_b|}, \quad (7)$$

was computed as the sum of the semantic relatedness scores, normalized by the sizes of the two buckets. The clustering algorithm terminated when the number of clusters between successive iterations remained unchanged.

2.5. Subgraph Ranking

The generated subgraphs are then ranked. Subgraphs containing more than one path are ranked in descending order, based on their *intra-cluster similarity*, which measures the compactness of the cluster. To compute this measure

$$sim_{intra}(B) = \frac{2 \cdot \sum_{p_i, p_j \in B, p_i \neq p_j} sr''_L(p_i, p_j)}{|B| \cdot (|B| - 1)}, \quad (8)$$

the aggregate of the relatedness score for each pair of paths ($p_i \neq p_j$) in a given cluster B is obtained and then normalized.

Singleton clusters consisting of only one path were ranked in ascending order using the measure of association rarity. That is, given a path p_i , an association $A(p_i)$, derived of the path, is the set of unique concepts in the path. Association rarity is the number of MEDLINE articles $f(A(p_i))$ that contain only the concepts in the path. For singleton paths, bucket rarity

$$r(B) = \frac{\sum_{p_i \in B} f(A(p_i))}{|B|} \quad (9)$$

is the same as association rarity, since $B = \{p_i\}$.

The ranked list of clusters is rendered to the user for inspection in the *Discovery Browsing Interface*. This interface is available for review online (live tool – <http://knoesis-hpco.cs.wright.edu/obvio/>, video demo – <http://bit.ly/obviodemov>). Concepts are color-coded based on semantic groups obtained from the BKR, while predicates are color-coded based on a locally developed coding scheme, since none exists for predicates in the BKR.

Using this approach, 8 out of 9 existing scientific discoveries were recovered. These well-known discoveries are: 1) *Raynaud - Fish Oil* (1986) [29], 2) *Magnesium - Migraine* (1988) [30], 3) *Somatomedin C - Arginine* (1990) [31], 4) *Indomethacin - Alzheimer's Disease* (1996) [32], 5) *Estrogen - Alzheimer's Disease* (1996) [33] 6) *Calcium-Independent Phospholipase A2 - Schizophrenia* (1998) [34], 7) *Chlorpromazine - Cardiac Hypertrophy* (2004) [14], 8) *Testosterone - Sleep* (2012) [22] and 9) *Diethylhexyl (DEHP) - Sepsis* (2013) [28]. In the next section the application of this approach for the rediscoveries is discussed.




Figure 4: Gaussian Distribution of Path Relatedness scores for three rediscovery scenarios

3. Experimental Results

Given the absence of a gold standard dataset in LBD research, knowledge rediscovery is considered a *de facto* standard for evaluating LBD systems. To assess the effectiveness of the context-driven subgraph method, both an evidence-based evaluation and a statistical evaluation were conducted, based on nine existing scientific discoveries. The evidence-based evaluation qualitatively determines the extent to which our approach is capable of rediscovering the known knowledge, while the statistical evaluation is intended to measure the likelihood that a domain expert might be motivated to explore an arbitrary subgraph generated by the system. Specifically, it measures the interestingness of a subgraph, by quantifying the rarity of associations in the subgraphs in MEDLINE. Associations that have never been mentioned in any MEDLINE article are considered most interesting and are called *zero-rarity associations (ZR)*. The obvious caveat is that rare associations are not necessarily all interesting. The next section discusses the evidence-based evaluation.

3.1. Evidence-Based Evaluation

The first aspect of the evidence-based evaluation reports on the number of intermediates from a discovery that could be retrieved by our system. The second aspect substantiates the meaning of each association using evidence from the literature. Such evidence can be derived first using the predicates of the semantic predications in the subgraph. However, when this is insufficient or contradictory, evidence is obtained using the provenance of the predications in MEDLINE. Additionally, queries can be composed and executed in PubMed to explore inferred associations, not explicitly stated in the subgraphs, as commonly practiced.

For each rediscovery scenario, no concept filters were specified, to exclude concepts based on semantic types or groups. A generic predicate filter, called the STRICT filter was applied uniformly by the system (not the user), across some experiments,

to exclude less informative UMLS predicates, such as ASSOCIATED.WITH, INTERACTS.WITH and AFFECTS. This limited degree of manual filtering is the extent of *a priori* knowledge required for subgraph generation in the system. Also, in the following tables, the letter *Y* (for yes) is used to indicate that the status *S* of an intermediate as ‘found directly in a subgraph at position *P* in the list of subgraphs. The symbol *Y** indicates that an intermediate was found through discovery browsing.

Due to space limitations, only three experiments are discussed in detail: 1) *Raynaud - Fish Oil*, 2) *Magnesium - Migraine* and 3) *Somatomedin C - Arginine*. The six remaining experiments are discussed briefly in Section 3.1.4. Further details on each experiment are available in [43] and in the following online supplementary materials: 1) the Obvio wiki page - (<http://wiki.knoesis.org/index.php/Obvio>), section on Automatic Subgraph Creation), 2) a video demo - <http://bit.ly/obvioidemo> and 3) a beta-version of the Obvio web application - <http://knoesis-hpco.cs.wright.edu/obvio/>. The next section discusses the application of our approach to rediscover the Raynaud - Fish Oil rediscovery.

3.1.1. Raynaud Syndrome – Dietary Fish Oils

In November 1985, American Information Scientist *Don R. Swanson (1924 – 2012)* explored the research question of the role of *Dietary Fish Oils* (from salmon, mackerel, albacore, etc.) in *Raynaud Syndrome*. Through the methods described in [29], Swanson discovered that “*dietary fish oil might ameliorate or prevent Raynaud’s syndrome.*” This is because *Dietary Fish Oils*: 1) inhibit *Platelet Aggregation*, 2) increase the flow of blood (by reducing *Blood Viscosity*) and 3) also have a regulatory effect on the smooth muscle (thereby preventing *Vasoconstriction* and stimulating *Vasodilation*). Each of these concepts is causally implicated in *Raynaud*.

We seeded our algorithm with three concepts as sources: 1) *Fish Oils (C0016157)*, 2) *Fish oil - dietary (C0556145)* and 3) *Eicosapentaenoic Acid (C0000545)* and two concepts as targets: 1) *Raynaud Disease (C0034734)* and 2) *Raynaud Phe-*

nomenon (C0034735). The corpus consisted of the relevant 61 full text articles discussed by Swanson [29] in the pre-November 1985 period. There were only 4 articles from the *Dietary Fish Oil* set, which were in the *Raynaud* set. The path length was set to 3 and no predicate filter was specified. These choices are consistent with the choices in our earlier experiments in [27], in which we rediscovered and decomposed this hypothesis by manually constructing the subgraphs, using domain expertise as context.




Figure 5: Subgraph1 ($k = 3, 3\sigma$) on Eicosapentaenoic Acid, Platelet Aggregation and Raynaud Syndrome

The algorithm terminated in less than 5 minutes, producing 4 subgraphs (and 134 singletons) at 2σ and one subgraph (and 164 singletons) at 3σ . There were 1035 unique concepts and 4143 unique predications in the predications graph and the candidate graph contained 171 paths of length 3. Figure 5 shows that at 3σ , subgraph1 directly contains the intermediate *Platelet Aggregation*, which many rediscovery approaches consider sufficient to constitute a rediscovery. However, to better substantiate the association, we utilize the predicates in the subgraph, together with the provenance of the predications in MEDLINE, along with traditional PubMed search, to provide evidence.

The predication, which states that [*Eicosapentaenoic Acid CONVERTS_TO Prostaglandins*] was extracted from the following corroborating sentence, in the **full text** of the following article [PMID6827988] by Harris et. al. The authors state that the “recent discovery that the prostaglandins derived from eicosapentaenoic acid have biological effects different than those derived from arachidonic acid (C20:4w6) has generated further interest in fish oils.” Two of the other 61 articles [PMID6321621, PMID6314583] contained this predication. Harris also refers to the 1979 article [PMID218223] by Needleman et. al., which suggests further that [*Eicosapentaenoic Acid CONVERTS_TO Prostaglandin (PGI₃)*] in its metabolic pathway. And the full text of 1985 article [PMID2997286] by von Schaky et. al. confirms that *Eicosapentaenoic Acid* produces *Prostaglandin (PGI₃)* and *Epoprostenol (Prostacyclin (PGI₂))*. von Schaky notes that “dietary EPA is transformed in vivo in humans into prostaglandins I₃, which is as active . . . as the vasodilatory and antiaggregatory prostaglandin I₂.”

The subgraph also contains the predication, which states that [*Eicosapentaenoic Acid DISRUPTS Platelet Aggregation*]. This predication was extracted from the full text of the article [PMID6320840] by Saynor et. al., who refers to the “Mechanisms underlying the inhibition of platelet aggregation by eicosapentaenoic acid and its metabolites.”

The predication [*Alprostadil DISRUPTS Platelet Aggregation*] was extracted from the full text of the article [PMID6302714] by Dyerberg et. al., who pointed out that another author⁷ “was the first to show that [*Prostaglandin E1*] PGE₁ inhibited platelet aggregation.” The previously article by von Schaky also alludes to this possibility.

Conversely, the predication [*Epoprostenol TREATS Raynaud’s Phenomenon*] was correctly extracted from two articles; by Dowd et. al. [PMID7037038], who discusses “Treatment of Raynaud’s phenomenon by intravenous infusion of prostacyclin (PGI₂)” and by Belch et. al. [PMID3883365], who discusses “Increased prostacyclin metabolites and decreased red cell deformability in patients with systemic sclerosis and Raynauds syndrome.” Since both *Alprostadil (PGE₁)* and *Epoprostenol (PGI₂)* are synthetic forms of *Prostaglandins*, it is plausible that both *Alprostadil* and *Epoprostenol* actually treat *Raynaud’s Syndrome* by disrupting *Platelet Aggregation*. Indeed, the 1982 article [PMID6890719] by Pardy et. al., obtained through a date-restricted MEDLINE query⁸, confirms that *Alprostadil (PGE₁)* treats *Raynaud Phenomenon*, instead of the weaker *INTERACTS_WITH* relationship, present in the subgraph. The role of *Platelet Aggregation* in causing *Raynaud*, which is inferred and not explicit in the subgraph, is easily confirmed using another MEDLINE query (*Platelet Aggregation AND Raynaud AND 1865:1985/11[DP]*), which yields the 1985 article [PMID3985417] by Soro et. al.

This subgraph together with discovery browsing suggest a richer relationship among *Eicosapentaenoic Acid*, *Platelet Aggregation* and *Raynaud Syndrome* than would be provided by their co-occurrence. Rather, it appears that one mechanism by which [*Eicosapentaenoic Acid TREATS Raynaud Syndrome*] is by stimulating a series of *Prostaglandins* (namely, *Prostaglandin I₃ (PGI₃)*, *Prostaglandin E1 (PGE₁)* and *Prostacyclin (PGI₂)*), which actually disrupt *Platelet Aggregation*.

An important observation is that the subgraph contains contradicting semantic predications. For example, the two predications [*Eicosapentaenoic Acid CONVERTS_TO Prostaglandins*] and [*Eicosapentaenoic Acid INHIBITS Prostaglandins*] are opposing. The full text of the article [PMID6827988] by Harris et. al., from which the predication [*Eicosapentaenoic Acid CONVERTS_TO Prostaglandins*] was extracted supports its claim. However, the full text of the lone article [PMID6301111] by Moncada from which the predication [*Eicosapentaenoic Acid INHIBITS Prostaglandins*] was extracted states that “It is clear, therefore, that both prostaglandin dependent and independent pathways of platelet aggregation are inhibited by EPA in vitro.” This is an incorrect extraction from SemRep. The author is noting that [*Eicosapentaenoic Acid INHIBITS Platelet Aggregation*], not *Prostaglandins* as the predication suggests. It is important to note that resolution of such discrepancies is part

⁷Kloeze, J. Prostaglandins, Proceedings of the 2nd Nobel Symposium, pp. 241-252 (BERTSTRÖM, S. and SAMUELSON, B., eds.) Almqvist and Wiksell, Stockholm, 1967.

⁸Query: *Alprostadil AND Raynaud AND 1865:1985/11[DP]*. Confirmed in search result #12

of the discovery browsing process, which requires adjudication by domain experts. We provide the infrastructure for achieving this through provenance.

The second intermediate *Blood Viscosity*, was found in the list of *zero-rarity* singletons (result #15 in Table 2). The actual singleton, which states that [*Eicosapentaenoic Acid DISRUPTS Blood Viscosity*], [*Ketanserin DISRUPTS Blood Viscosity*], [*Ketanserin TREATS Raynaud Disease*], suggests a causal relationship between *Blood Viscosity* and *Raynaud Syndrome*. This inferred relation that [*Blood Viscosity CAUSES Raynaud Syndrome*] is confirmed in the 1984 article [PMID6707529] by Larcane et. al through a MEDLINE search. The statement [*Ketanserin DISRUPTS Blood Viscosity*] is verified in the following articles [PMID401574], [PMID6303363] and [PMID2412054]. Likewise, the predication [*Ketanserin TREATS Raynaud Disease*] can be verified in the article [PMID6432198] by Roald et. al. and also [PMID6209510] by Bounameaux et. al.

Table 2 shows the number of intermediates rediscovered for this experiment compared with 4 other approaches. The intermediate *Vascular Reactivity* (in reference to *Vasoconstriction*) was not found explicitly by our approach (although can be inferred from the article [PMID2997286] by von Schacky et. al.). This is not completely unexpected, since it is known from our reports in [27] that SemRep interprets “*Vascular*” and “*Reactivity*” as separate concepts. Hristovski in [17] was also subject to the same limitation.

Srinivasan [7] found all three intermediates in the top 2 of the top 30. However, note that Srinivasan’s approach relies on *a priori* knowledge of the semantic types of the intermediates for filtering and is manually intensive. Additionally, that approach does not create complex subgraphs, nor does it provide evidence for the meaning of associations using predicates. Hristovski et. al. [17] and Weeber et. al. [4] also require considerable domain expertise, particularly for specification of *a priori* relations (i.e., semantic types and discovery patterns). Gordon and Lindsay [6] find intermediates but make no attempt to elucidate the meaning of associations.




Figure 6: Subgraph1 ($k = 3, 2\sigma$) on Dietary Fish Oils - Raynaud Syndrome (Blood Platelets/Prostaglandins)

To illustrate that our subgraphs capture different thematic dimensions of association between two concepts, consider the four subgraphs at 2σ . Subgraph1 in Figure 6a is similar to subgraph1 (at 3σ) except that it includes the three additional intermediates, *TIMP1*, *TIMP1 protein, human* and *Thromboembolism*. This is naturally due to a lower threshold for path relatedness. By inspection, this subgraph elucidates the as-

sociation between *Dietary Fish Oils* and *Raynaud Syndrome* through *Blood Platelets/Prostaglandins*, similar to the previous subgraph.




Figure 7: Subgraph2 ($k = 3, 2\sigma$) on Dietary Fish Oils - Raynaud Syndrome (Pharmaceuticals)

Subgraph2 (shown in Figure 7) associates *Dietary Fish Oils* and *Raynaud Syndrome* from the perspective of *Pharmaceuticals*, including *Nifedipine*, *Pentifylline*, *Thyrocalcitonin*, and *Trinitrin* detailed especially in the article [PMID6352267] by Kahan et. al., from which the predication [*Nifedipine TREATS Raynaud Phenomenon*] was extracted. *Epoprostenol* is the synthetic form of *Prostacyclin (PGI₂)*.




Figure 8: Subgraph3 ($k = 3, 2\sigma$) on Dietary Fish Oils - Raynaud Syndrome (Lipids/Fatty Acids)

Subgraph3 in Figure 8 discusses the role of various Fatty Acids, which associate *TIMP1*, *Epoprostenol*, *Efasol* and *Evening Primrose* (see [PMID4082084, PMID6318123, PMID6321621]).




Figure 9: Subgraph4 ($k = 3, 2\sigma$) on Eicosapentaenoic Acid, Platelet Aggregation and Raynaud Syndrome (Blood Platelets)

Subgraph4 in Figure 9, which focuses more on *Cellular Activity* at the level of *Blood Platelets* involving *Thromboembolism*, is subsumed by subgraph1. Currently, subgraph subsumption has not been addressed in this work and remains a system limitation, discussed in Section 4. In the next section, the *Migraine - Migraine* experiment is discussed.

Table 2: Comparison of rediscoveries with other approaches for Raynaud Syndrome - Dietary Fish Oils

Scenario	Intermediate(s)	Cameron		Srinivasan [7]		Weeber [4]		Gordon [3]		Hristovski [17]	
		S	P	S	P	S	P	S	P	S	P
Raynaud Syndrome - Dietary Fish Oils	Blood Viscosity	Y*	ZR-15	Y	2	Y	-	Y	5	Y	8
	Platelet Aggregation	Y	1	Y	1	Y	-	Y	6	Y	17
	Vascular Reactivity	-	-	Y	1	Y	-	Y	19	-	-

3.1.2. Magnesium – Migraine

In August 1987, Swanson explored the research question of the role of *Magnesium* in *Migraine Disorder*. Through the methods described in [30] he discovered 11 neglected connections between *Magnesium* and *Migraine*. He found that *Magnesium* deficiency might exacerbate *Migraine* due to complications involving *Stress (Type A personality)*, *Spreading Cortical Depression*, *Epilepsy*, *Platelet Aggregation*, *Serotonin*, *Substance P*, *Inflammation*, *Vasoconstriction*, *Prostaglandin* formation and *Hypoxia*. Also, as a natural calcium channel blocker, *Magnesium* may further prevent *Migraine* attacks.

We seeded our algorithm with *Magnesium* (C0024467) as the source and *Migraine Disorders* (C0149931) as the target. The path length was 2 and no predicate filter was used, to be more consistent with the discovery. The corpus consisted of more than 47,000 articles from the pre-August 1987 period (i.e., 41,507 abstracts on *Magnesium* and 6,171 on *Migraine*, 7 overlapping). There were 14697 unique concepts, 73,960 predications in the predications graph and 256 distinct paths of length 2 in the candidate graph. The algorithm terminated in less than one hour, producing 25 subgraphs (and 151 singletons) at 2σ and 6 subgraphs (and 231 singletons) at 3σ .




Figure 10: Subgraph1 ($k = 2, 2\sigma$) Magnesium - Migraine

It was known from the 1973 article [PMID4725298] by Vosgeru (one of the 7 overlapping) that *Magnesium Glutamate* was used to treat *Migraine*. Figure 10 shows that the intermediate Serotonin was found in subgraph1 at 2σ . The lone article [PMID3629724] by Pertseva et. al. from which the predication [*Magnesium INTERACTS_WITH Serotonin*] was extracted, is inconclusive. According to Swanson this association should be that [*Magnesium INHIBITS Serotonin*]. The article [PMID3512233] by Houston et. al. from which the predication [*Serotonin CAUSES Migraine*] was extracted (among three others), suggests that elevated levels of *Serotonin* can induce *Vasoconstriction*, which causes *Migraine*. Houston explicitly states that “much evidence has implicated serotonin (5-

hydroxytryptamine) in the pathogenesis of migraine.” The article further notes that *Serotonin* is released from *Platelet Aggregation* and might reach sufficient levels to exacerbate *Migraine*, as noted by Swanson. The 1987 article [PMID2440758] by Briel et. al. (through a MEDLINE search) confirms that *Magnesium* inhibits *Platelet Aggregation*. It follows that elevated *Magnesium* levels may inhibit both *Serotonin* and *Platelet Aggregation*, and so treat *Migraine*.




Figure 11: Subgraph4 ($k = 2, 2\sigma$) Magnesium - Migraine

Figure 11 shows subgraph4, which contains the intermediate *Prostaglandins* between *Magnesium* and *Migraine*. The lone article [PMID3871957] by Friedlander et. al. from which the predication [*Prostaglandins INTERACTS_WITH Magnesium*] was extracted, suggests a decrease in prostaglandin synthesis is accompanied by lower levels of magnesium (and calcium). This is based on the title: “Decreased calcium and magnesium urinary excretion during prostaglandin synthesis inhibition in the rat” as noted by Swanson. The 1986 article [PMID3016750] by Nigam et. al. confirms that [*Magnesium STIMULATES Prostaglandins*] as suggested by Swanson. The article [PMID89390] by Hakkarainen et. al. from which the predication [*Prostaglandins ASSOCIATED_WITH Migraine Disorders*] was extracted (among only three others) states that “*Tolfenamic acid* (a potent inhibitor of prostaglandin biosynthesis) was effective in treating acute migraine attacks.” The specific role of *Prostaglandins* in *Migraine* was unclear however, even after discovery browsing. Swanson suggested that [*Prostaglandins INHIBITS Migraine*].

Figure 12 shows that the intermediate *Vascular Disease* was found explicitly in subgraph9. The title of the article [PMID4260015] by Wustenberg et. al. from which the predication [*Magnesium ASSOCIATED_WITH Vascular Disease*] was extracted, suggests a role for magnesium in vascular reactivity. The title of the article reads in part, “... Findings in magnesium metabolism in vascular diseases.” Similar to the predi-

Table 3: Comparison of rediscoveries with other approaches for Magnesium - Migraine

Scenario	Intermediate(s)	Cameron		Srinivasan [7]		Weeber [4]		Blake [37]		Gordon [3]	
		S	P	S	P	S	P	S	P	S	P
Magnesium - Migraine	Calcium Channel Blockers	Y	22	Y	3	Y	-	Y	10	Y	1
	Epilepsy	Y*	9	-	-	Y	-	Y	8	Y	3
	Hypoxia	-	-	Y	5	-	-	Y	6	Y	77
	Inflammation	Y*	ZR-3	Y	2	Y	-	Y	170	Y	82
	Platelet Activity	Y*	1	Y	2	Y	-	Y	2	Y	8
	Prostaglandins	Y	4	Y	1	Y	-	Y	42	Y	27
	Type A Personality	-	-	Y	1	Y	-	Y	23	-	-
	Serotonin	Y	1	Y	1	Y	-	Y	5	Y	1
	Cortical Depression	-	-	Y	6	-	-	Y	45	-	-
	Substance P	-	-	Y	18	Y	-	Y	38	Y	23
Vascular mechanisms	Y	9	Y	1	Y	-	Y	46	Y	16	




Figure 12: Subgraph9 ($k = 2, 2\sigma$) Magnesium - Migraine

cation with *Serotonin*, it is unclear from this title that [*Magnesium INHIBITS Vasoconstriction*] as noted by Swanson. On the other hand, the article [PMID1153064] by Domzal, from which the predication [*Migraine Disorders ISA Vascular Diseases*] was extracted (among three others), suggests that migraine is also a vascular disorder, although primarily a cerebral disorder. The lone article [PMID3945397] by Coppeto et. al. from which the predication [*Migraine Disorders AFFECTS Vascular Diseases*] was extracted provides more compelling evidence by linking migraine and vascular retinopathy as suggested by Swanson. Coppeto reported that “two migraineurs suffered sudden, persisting loss of vision from retinal vascular occlusion.” This effect is consistent with the observation by Houston et. al. from the article [PMID3512233] on *Serotonin* from subgraph1. Salati et. al. in [PMID6225285], from which the predication [*Migraine Disorders ISA Vascular Diseases*] was extracted, noted a dependency among *Migraine*, *Vascular diseases*, *Epilepsy* and *Autoscopy* (outer-body hallucination).

The two calcium channel blockers, *Nifedipine* and *Verapamil* were the only intermediates in subgraph22 (not shown). All three articles [PMID2425960, PMID3673084, PMID6539877] confirmed that these calcium channel blockers treat *Migraine* as suggested by Swanson. The article [PMID537283] by Khoda et. al. from which the predication [*Verapamil INTERACTS WITH Magnesium*] was extracted suggested that *Magnesium* inhibits *Verapamil* as noted by Swanson.

The intermediate *Hydrocephalus* (accumulation of fluid in

the brain), which leads to *Brain Edema* (referred to as or inflammation by Swanson), was found among the zero-rarity associations (see Table 3). The remaining intermediates *Hypoxia*, *Spreading Cortical Depression*, *Stress (Type A Personality)* and *Substance P* were not found among the subgraphs.

Interestingly, only subgraph22 on the calcium channel blockers was a complex subgraph in which existing knowledge was recovered. While several intermediates related to *Vascular Reactivity*, such as *Vasospasm*, *Vascular Function*, *Vasoconstriction* and *Vascular Disease* exists, their shared context did not meet our threshold for path relatedness and hence they were not grouped into the same cluster. The shortcomings of SemRep in extracting *Vascular Reactivity* may also have been a limiting factor. Still, altogether 10 out of the 25 subgraphs contained complex associations.




Figure 13: Subgraph7 ($k = 2, 2\sigma$) Magnesium - Migraine

Subgraph7 (shown in Figure 13) for example, links *Theophylline* and *Caffeine*, with *Magnesium* and *Migraine*, which have different semantic types, but belong to the general group of *Stimulants*. Subgraph6 (not shown) associates *Epinephrine* and *Glucose* from the perspective of *Metabolism*. Table 3 shows that ultimately, 7 out of the 11 associations found by Swanson could be found using our approach.

3.1.3. Somatomedin C – Arginine

In April 1989, Swanson explored the research question of the role of the dietary amino acid *Arginine*, in *Growth* along with the protein *Somatomedin C* (also called *Insulin-Like Growth Factor 1 (IGF1)*). Through the methods discussed in

[31], Swanson discovered 4 implicit connections between *Somatomedin C* and *Arginine*. He found that *Arginine* intake could: 1) stimulate *Growth* and protein synthesis, 2) promote *Wound Healing* and cell regeneration, 3) facilitate nutritional repletion and overcoming *Malnutrition* and 4) improve *Body Mass* (and *Weight*), especially in the elderly and debilitated.

We seeded our algorithm with *Somatomedins* (C0037657) and *Insulin-Like Growth Factor 1* (C0021665) as the sources, and *Arginine* (C0003765) as the target. The corpus consisted of more than 11,000 articles (819 on *Somatomedins* and 10,698 on *Arginine* (with 53 overlapping), in the pre-April 1989 period. The path length was set to 2, this time with the STRICT predicate filter. There were 5195 concepts and 17,058 predications in the predications graph and 239 distinct paths in the candidate graph. The algorithm terminated in less than one hour producing 10 subgraphs (and 153 singletons) at 2σ and 7 subgraphs (and 205 singletons) at 3σ .




Figure 14: Subgraph5 ($k = 2, 3\sigma$) Somatomedin C – Arginine

Figure 14 shows the intermediate *Growth Hormone* in subgraph5 at 3σ . The sequence of predications [*Arginine STIMULATES Growth Hormone*], and [*Growth Hormone STIMULATES Somatomedins*] is entirely correct and requires no further proof (in terms of rediscovery). Still, for verification, we confirmed in the article [PMID6394628] by Chew et. al. that dietary *Arginine* stimulates the release of *Growth Hormones*. These *Growth Hormones* then stimulate the production of *Somatomedin C (IGF1)*, which leads to cell growth and increased body size and muscle (i.e., protein synthesis), as noted in article [PMID7194347] by Clemmons et. al. The same association is captured in subgraph6 at 2σ (not shown).

In subgraph5, several articles from which the seemingly spurious predication [*Arginine TREATS Child*] was extracted, upon investigation, were shown to actually discuss *Glucagon* and *Insulin*. This includes the article [PMID7204541] by Blethen et. al. whose title is “*Plasma somatomedins in children with hyperinsulinism.*” Likewise, the article [PMID6205015] by Binoux et. al. from which the predication [*Arginine TREATS Rattus norvegicus*] was extracted, discusses observations regarding *Insulin-like Growth Factor 1* in the serum of rats. The article [PMID7007553] by Ashby et. al. from which the same predication was extracted, discusses the effects of *Progesterone* and *Insulin* in rats, resulting from *Glucose* and *Arginine* stimulation. Based on these observations, it is reasonable to conclude

that this subgraph captures the shared context of role of *Insulin* in *Somatomedin C* and *Arginine*.

Subgraph7 at 3σ (not shown) contains the concept *Growth* as an intermediate instead of *Growth Hormone* (similar to subgraph2 at 2σ , also not shown). The sequence of predications [*IGF1 CAUSES Growth*] and [*Growth PRODUCES Somatomedins*], is interesting because the article [PMID3748655] by van Buul-Offers et. al. from which the predication [*IGF1 CAUSES Growth*] was extracted states that IGF1 “*increases body length and weight, as well as the growth of several organs of Snell dwarf mice,*” which is consistent with Swansons report. The association between *Malnutrition* and *Somatomedin* production was found in the article [PMID7023246] by McCumbee et. al., from which the predication [*Growth PRODUCES Somatomedins*], was extracted. No obvious association to *Wound Healing* was found using our methods. Table 4 shows that 3 out of 4 intermediates could be found using our approach.

Table 4: Comparison of rediscoveries with other approaches for Somatomedin C - Arginine

Scenario	Intermediate(s)	Cameron		Srinivasan [7]	
		S	P	S	P
Somatomedin C - Arginine	Growth Hormone	Y	5	Y	1
	Body Weight	Y*	7	Y	4
	Malnutrition	Y*	7	-	-
	Wound healing	-	-	Y	4

3.1.4. Remaining Experiments

This section briefly presents the results for the remaining 6 rediscoveries attempted. Each intermediate marked as rediscovered was found using predicates, provenance and discovery browsing as previously done.

Scenario 4: For the *Indomethacin - Alzheimer’s Disease* discovery [32] by Smalheiser and Swanson in 1995, there were 15 subgraphs at 2σ . Srinivasan found all 8 intermediates, while we only recovered 6 out of 8 intermediates from subgraphs 2, 3, 4 and 14 (shown in Table 5). Recall that all our subgraphs are all automatically generated.

Table 5: Comparison of rediscoveries with other approaches in the literature for Indomethacin - Alzheimer’s Disease

Scenario	Intermediate(s)	Cameron		Srinivasan [7]	
		S	P	S	P
Indomethacin - Alzheimer’s Disease	Acetylcholine	Y	4	Y	2
	Lipid peroxidation	Y*	2	Y	4
	M2-muscarinic	-	-	Y	3
	Membrane Fluidity	-	-	Y	10
	Lymphocytes	Y*	14	Y	4
	Thyrotropin	Y	ZR-20	Y	9
	T-lymphocytes (T-Cells)	Y*	3	Y	5

Scenario 5: For *Estrogen - Alzheimer’s Disease* [33] by Smalheiser and Swanson in 1995, we found 3 out of 8 interme-

Table 6: Comparison of rediscoveries with other approaches in the literature for Estrogen - Alzheimer’s Disease

Scenario	Intermediate(s)	Cameron	
		S	P
Estrogen - Alzheimer’s Disease	Antioxidant activity	Y*	4
	Alipoprotein E (ApoE)	Y*	3
	Calbindin D28k	Y	4
	Cathepsin D	–	–
	Cytochrome C oxidase	–	–
	Glutamate	–	–
	Receptor Polymorphism	–	–
	Superoxide Dismutase	–	–

diates from 3 subgraphs at 2σ , as shown in Table 6. Srinivasan did not attempt this experiment.

Table 7: Comparison of rediscoveries with other approaches in the literature for Calcium-Independent PLA2 - Schizophrenia

Scenario	Intermediate(s)	Cameron		Srinivasan [7]	
		S	P	S	P
Calcium-Independent PLA2 - Schizophrenia	Oxidative stress	Y*	3	Y	3
	Selenium	Y*	3	–	–
	Vitamin E	Y*	3	–	–

Scenario 6: For *Calcium-Independent PLA2 - Schizophrenia* [34] by Smalheiser and Swanson in 1997, our algorithm produced 10 subgraphs at 2σ , all of which were singletons. Here, our results are comparable to Srinivasan’s, except that we are able to retrieve the article [PMID7782894] by Kuo et. al. deemed crucial to the discovery, through discovery browsing from singleton2. The seemingly innocuous singleton in subgraph2, which states that [*Phospholipase A2 INHIBITS Proteins*] [*Proteins CAUSES Schizophrenia*] leads to the article [PMID7739414] by Berry, from which the predication [*Proteins CAUSES Schizophrenia*] was extracted. The article shows that the specific protein discussed was the *selenium transport protein Selenoprotein P*, as noted by Smalheiser. The article by Kuo is #4 in the search results of a MEDLINE search for *Phospholipase A2 AND Selenium AND 1865:1997[DP]*.

Scenario 7: For *Chlorpromazine - Cardiac Hypertrophy* [14] by Wren et. al. in 2002, there were 14 subgraphs at 2σ . The intermediate *Isoproterenol* was found in subgraph12 (as shown in Table 8). The article [PMID6165961] by Rossi et. al. from which the predication [*Chlorpromazine INHIBITS Isoproterenol*] was extracted, together with the article [PMID203365] by Tsang et. al. from which the predication

Table 8: Comparison of rediscoveries with other approaches in the literature for Chlorpromazine - Cardiac Hypertrophy

Scenario	Intermediate(s)	Cameron	
		S	P
Chlorpromazine - Cardiac Hypertrophy	Calcineurin	Y	5
	Isoproterenol	Y	12

Table 9: Comparison of rediscoveries with other approaches in the literature for Testosterone - Sleep

Scenario	Intermediate(s)	Cameron		Goodwin [21]	
		S	P	S	P
Testosterone - Sleep	Cortisol/Hydrocortisone	Y	10	Y	4

[*Isoproterenol CAUSES Cardiomegaly*] was extracted, substantiated these predications. Subgraph5 contained the predications [*Chlorpromazine INHIBITS Calcineurin*] extracted from the article [PMID9001710] by Gong et. al. and the predication [*Calcineurin CAUSES Cardiac Hypertrophy*] extracted from several articles, including [PMID9568714, PMID10679475, PMID11248077, PMID11773940, PMID10189350].

Scenario 8: For *Testosterone - Sleep* [22] by Miller and Rindfleisch in 2011, which articulates that “*testosterone enhances sleep quality by inhibiting cortisol*,” we found 11 subgraphs at 2σ and 10 subgraphs at 3σ . *Cortisol (or Hydrocortisone)* was found in subgraph7 at 3σ and also in subgraph11 at 2σ . The article [PMID8548511] by Kern et. al. confirmed that [*Hydrocortisone DISRUPTS Sleep*], while the crucial article [PMID15841103] by Rubinow et. al., noted by Miller, confirms that [*Testosterone INHIBITS Hydrocortisone*].

Scenario 9: For *Diethylhexyl Phthalate (DEHP) - Sepsis* [28] by Cairelli and Rindfleisch in 2013, which articulates one possible mechanism for the obesity paradox [38], we did not find the intermediate *PParGamma* altogether.

In summary, several approaches succeed in providing automation for finding intermediates. These approaches leverage keyword-based, concept-based relations-based, graph-based and hybrid techniques. Many also provide predicates between concepts, while more recent approaches are able to substantiate intermediates with provenance in MEDLINE. The main innovation of our approach is that we are able to retrieve and substantiate existing discoveries, on different thematic dimensions, using implicit and explicit context as suggested by Gordon and Dumais [2], not frequency, graph metrics or specificity. To the best of our knowledge, an approach that has rediscovered as many intermediates, with such degree of automation and substantiation of the knowledge, has never been developed. In the next section the statistical evaluation is presented.

3.2. Statistical Evaluation

In the previous section, we showed that our context-driven subgraph method facilitated the rediscovery of 8 existing discoveries with their substantiation in MEDLINE. While these are encouraging results, one might argue that our experiments were biased since we knew the intermediates to be found in the first place. Hence, it was easy to find them in the subgraphs. A more important question is *how interesting are subgraphs in general, such that an arbitrary domain expert might be motivated to explore them altogether?* To address this question, we conducted a statistical evaluation, which uses *association rarity* to compute *interestingness*. If the interestingness score of the subgraphs across an entire experiment is low, then the rediscoveries were fortuitous and the associations that led to the

rediscoveries were serendipitous, rather than systematic. While this not a complete loss, it is still less than ideal.

To perform this evaluation, for each path in each subgraph across the 8 rediscoveries (excluding singletons), a PubMed query was executed using the eUtils Web Service⁹. This was used to determine the number of documents that contain the association in MEDLINE, with the date restriction enforced. For example, for the path [*Arginine STIMULATES Growth Hormone*], [*Growth Hormone STIMULATES Somatomedins*], the query “*Arginine AND Growth Hormone AND Somatomedins AND 1865:1989/04[DP]*” was composed, where *Arginine*, *Growth Hormone*, and *Somatomedins* represent an association. The rarity

$$r(E) = \frac{\sum_{p_i \in E} f(A(p_i))}{|E|} \quad (10)$$

of a set of associations across all subgraphs in an experiment E , is computed as the average of the association rarity, where $f(A(p_i))$ is the frequency of a unique association in MEDLINE. The interestingness of an experiment

$$I(E) = \frac{1}{r(E) + 1} \quad (11)$$

was computed as the normalized reciprocal of rarity.

Table 10 shows the rarity and interestingness scores for each of the eight successful rediscoveries. For the *Raynaud Syndrome – Dietary Fish Oils* experiment, there were 10 unique intermediates/associations among the 4 subgraphs at 2 σ , all of which had a zero-rarity in MEDLINE. This is not surprising, since Swanson noted in [29] that only four articles from the *Raynaud* literature overlapped with the *Fish Oil* literature by 1986. The rarity of these subgraphs is therefore 0.00, and the interestingness is 1 (meaning absolutely interesting).

For *Magnesium – Migraine* there were 48 unique associations. The most commonly known intermediates were *Hypertensive Disease* (3), *Individual* (3) and *Vascular Diseases* (4), respectively among a total of 27 documents. The overall rarity of the subgraphs in the experiment was therefore $27/48 = 0.56$ and the interestingness is 0.64.

For *Somatomedin C – Arginine* there were 18 unique associations/intermediates among a total of 306 documents. The most commonly known intermediates were *Child* (16), *Somatropin* (63) and *Growth Hormone* (63). There were only two zero-rarity associations, which were from the intermediates *Mus* (0) and *Falls* (0). Clearly these are not interesting. Not surprisingly, the overall interestingness score of these subgraphs was $306/18 = 17$ and the interestingness is low (0.06). This suggests that this field was better studied than others. It also partially supports the observation by Gordon and Dumais [2] that while frequency of intermediates may be sufficient for finding novel intermediates in some cases, it may be insufficient to capture the related concepts that elucidate complex associations.

There were 21 unique associations for *Indomethacin – Alzheimers*. *Hydrogen Peroxide* (2), *Interleukin-1* (2) and *Free*

Radicals (3) were the most commonly known intermediates among a total of 9 documents. The overall rarity score was $9/21 = 0.43$ and the interestingness is 0.70.

For *Estrogen – Alzheimers* there were 42 unique associations, with 36 zero-rarity associations. *Metabolism* (6), *Dementia* (10) and *Senile dementia* (10) were the most commonly known intermediates among a total of 36 documents. The rarity score is $36/42 = 0.86$ and the interestingness is 0.54.

For *Calcium-Independent PLA2 – Schizophrenia* there were 10 unique intermediates/associations (singletons described in Section 4.1.6), each of which was zero-rarity. Hence, the rarity of this subgraph is 0.00 and the interestingness was high (1.0).

For *Chlorpromazine – Cardiac Hypertrophy* there were 21 unique associations, and 19 at zero-rarity. The most commonly known were *Catecholamines* (1) and *Hypertensive disease* (1) among a total of 2 documents. The rarity is therefore $2/21 = 0.10$ and the interestingness is high (0.91).

For *Testosterone – Sleep*, there were 61 unique association-s/intermediates and 20 at zero-rarity. The most commonly known were *Proteins* (63), *Symptoms* (91) and *Hormones* (207) among a total of 654 documents. The overall rarity score was therefore $654/61 = 10.72$ and the interestingness is low (0.09). This is not surprising, since these two domains (*Testosterone* and *Sleep*) are fairly well studied. This is another scenario that suggests frequency may not be as effective for finding the related concepts that elucidate complex associations.

Across all 8 rediscoveries, the average rarity score is therefore 3.71 and the average interestingness was 0.62. This suggests that an association chosen at random from the rediscoveries is likely to be known to only approximately 4 documents in MEDLINE. Such a low rarity score suggests that the subgraphs themselves might be quite interesting to a domain expert. This is however not surprising, since most of the discoveries, at the time when made would have been inherently interesting situations and possibly not well studied in the literature. *Testosterone – Sleep* (2011) and *Somatomedin C – Arginine* (1990) are exceptional.

4. Discussion

This paper showed that the use of implicit and explicit context to find and elucidate associations among concepts along multiple thematic dimensions is effective for LBD. However, our approach has several limitations. The first limitation is the assumption that the context of a semantic predication, expressed in terms of the distribution of MeSH descriptors is reliable for generating meaningful subgraphs. Not all MeSH descriptors assigned to an article are relevant to all its semantic predications, and hence the predication context vectors could be noisy. Ideally, direct mappings between semantic predications and MeSH descriptors could help resolve this discrepancy. Since, such mappings are unavailable our specification of context is subject to limitations of distributional semantics.

The second limitation is the degree of domain expertise still required for discovery browsing. Although impractical to eliminate the need for domain expertise, one improvement would be

⁹eUtils Help - <http://www.ncbi.nlm.nih.gov/books/NBK25500/>

Table 10: Rarity and Interestingness score of the subgraphs in the rediscoveries

Experiment	# Unique Associations	MEDLINE Frequency	r(E)	I(E)
Raynaud Syndrome - Dietary Fish Oils	10	0	0.00	1.00
Magnesium - Migraine	48	27	0.56	0.64
Somatomedin C - Arginine	18	306	17.00	0.06
Indomethacin - Alzheimer’s Disease	21	9	0.43	0.70
Estrogen - Alzheimer’s Disease	42	36	0.86	0.54
Calcium Independent PLA2 - Schizophrenia	10	0	0.00	1.00
Chlorpromazine - Cardiac Hypertrophy	21	2	0.10	0.91
Testosterone - Sleep	61	654	10.72	0.09
Average	29	129	3.71	0.62

providing additional background knowledge to supplement the subgraphs where appropriate. In this way, assertional knowledge from the literature would be complemented with definitional knowledge from structured knowledge sources (though deep integration). Metrics for determining interesting neighboring concepts in background knowledge need to be developed for concepts in the subgraph to overcome this limitation.

Another limitation is the inability to systematically detect contradicting semantic predications. While the provenance of predications in MEDLINE allows domain experts to adjudicate, a method for resolving conflicting predications could be beneficial. We believe that temporal analysis of semantic predications could enable conflict resolution. However, since many unresolved paradoxes inherent in science itself are reported in the literature, it is unclear whether one might reliably detect and resolve such contradictions automatically, using temporal, statistical and/or semantic approaches.

The reliability of the statistical evaluation is also another limitation of our approach. Rare associations are generally interesting but not always. While alternative methods for conducting statistical evaluation for LBD have been discussed [39], it is cumbersome to coordinate cut-off dates for each predication across the rediscoveries. The suggested techniques are therefore impractical to implement. We use association rarity to indicate interestingness, similar to existing research [20, 7].

A number of technical limitations exist in our approach. The first technical limitation is the manual selection of a threshold for MeSH semantic similarity based on dice similarity. While dice is advantageous because it is easy to implement, other similarity metrics and more principled ways of computing the threshold should be explored. Likewise, the threshold for path relatedness, which is based on the second (and third) standard deviation from the mean of the Gaussian distribution, could be unreliable. Our results show that the data distributions only approximate to Gaussian. The p-values from the χ^2 test of the three Gaussian distribution in Figure 4 indeed more than the 0.05 value normally considered acceptable. To overcome this limitation, we anticipate that path relatedness could be recomputed relative to the minimum relatedness score. Torvik et. al. [12] and Smalheiser et. al. [15] implemented an approach based loosely on this idea, which normalized the distribution, using a mixture of Gaussian models.

Across some experiments, we utilized predicate filters

to eliminate non-informative relationships (such as ASSOCIATED_WITH, INTERACTS_WITH, AFFECTS, etc). This is a compromise to achieve scalability. Ideally, the system should not require any predicate filters. In fact, the omission of some predicates may be responsible for low recall in some of our experiments. Still, given that most experiments terminated in less than one hour, higher recall may not be too costly for performance. With the emergence of big data infrastructure, the performance limitations of our clustering may be resolved using additional computational resources.

The choice of HAC could be considered another limitation. HAC was selected because it is an unsupervised, deterministic clustering algorithm, for which the number of clusters does not have to be known or specified *a priori*. The time complexity of HAC is $\Theta(N^2 \log N)$ in the best case. While approaches, such as those by Ramakrishnan et. al. [20] and van der Eijk et. al. [23] may be applicable for subgraph creation, it is unclear how they might be adapted to generate complex subgraphs along multiple thematic dimensions.

These and other limitations suggest the next steps in this research. In future, labels for subgraphs should be provided. This is a crucial task, since our approach is predicated on the idea that each subgraph captures a different thematic dimension of association between two concepts. Additionally, a comparative study using full text, compared to titles and abstracts, could be useful. However, full text is only available on a limited scale.

5. Conclusion

Leveraging rich representations of textual content from scientific literature based on implicit and explicit context can provide effective means for literature-based discovery, as illustrated in this paper. This paper also shows that these rich representations were important in facilitating the rediscovery of 8 out of 9 well-known associations and their substantiation. The approach advances LBD research specifically because it uses notions of context and shared context to facilitate making discoveries from scientific literature, which do not rely on statistical frequency, graph metrics or specificity. A beta-version of the Obvio web application is available online for optional viewing (<http://knoesis-hpco.cs.wright.edu/obvio/>), along with various other resources (wiki page -

<http://wiki.knoesis.org/index.php/Obvio>, video demo - <http://bit.ly/obvioidemo>), which help put the contributions of this research into perspective.

Conflict of interest: None.

6. Acknowledgement

This research was supported in part by the Intramural Research Program of the US National Institutes of Health, National Library of Medicine. We would especially like to thank Pavan Kapanipathi, Wenbo Wang and Shreyansh Bhatt for their insightful feedback on many aspects of this work. We also thank Swapnil Soni, Nishita Jaykumar, Vishnu Bompally, Gary A. Smith, Drashti Dave, Swapna Abhyankar, Mike Cairelli and Gaurish Anand, who contributed to other aspects of this work.

References

- [1] Sheth AP, Ramakrishnan C, Thomas C. Semantics for the semantic web: The implicit, the formal and the powerful. *Int J Semantic Web Inf Syst* 2005;1(1):1–18.
- [2] Gordon MD, Dumais ST. Using latent semantic indexing for literature based discovery. *JASIS* 1998;49(8):674–85.
- [3] Gordon MD, Lindsay RK. Toward discovery support systems: A replication, re-examination, and extension of swanson’s work on literature-based discovery of a connection between raynaud’s and fish oil. *JASIS* 1996;47(2):116–28.
- [4] Weeber M, Klein H, de Jong-van den Berg LTW, Vos R. Using concepts in literature-based discovery: Simulating swanson’s raynaud-fish oil and migraine-magnesium discoveries. *JASIST* 2001;52(7):548–57.
- [5] Weeber M, Vos R, Klein H, de Jong-van den Berg LTW, Aronson AR, Molema G. Case report: Generating hypotheses by discovering implicit associations in the literature: A case report of a search for new potential therapeutic uses for thalidomide. *JAMIA* 2003;10(3):252–9.
- [6] Lindsay RK, Gordon MD. Literature-based discovery by lexical statistics. *JASIS* 1999;50(7):574–87.
- [7] Srinivasan P. Text mining: Generating hypotheses from medline. *JASIST* 2004;55(5):396–413.
- [8] Hristovski D, Stare J, Peterlin B, Dzeroski S. Supporting discovery in medicine by association rule mining in Medline and UMLS. *Studies in health technology and informatics* 2001;84(Pt 2):1344–8.
- [9] Pratt W, Yildiz MY. LitLinker: capturing connections across the biomedical literature. In: *Proceedings of the 2nd international conference on Knowledge capture*. K-CAP ’03; NY, USA: ACM; 2003, p. 105–12.
- [10] Swanson DR, Smalheiser NR. An interactive system for finding complementary literatures: a stimulus to scientific discovery. *Artificial Intelligence* 1997;91(2):183 – 203.
- [11] Yetisgen-Yildiz M, Pratt W. Using statistical and knowledge-based approaches for literature-based discovery. *Journal of Biomedical Informatics* 2006;39(6):600–11.
- [12] Torvik VI, Smalheiser NR. A quantitative model for linking two disparate sets of articles in medline. *Bioinformatics* 2007;23(13):1658–65.
- [13] Wren JD. Extending the mutual information measure to rank inferred literature relationships. *BMC Bioinformatics* 2004;5:145.
- [14] Wren JD, Bekeredian R, Stewart JA, Shohet RV, Garner HR. Knowledge discovery by automated identification and ranking of implicit relationships. *Bioinformatics* 2004;20(3):389–98.
- [15] Smalheiser NR, Torvik VI, Zhou W. Arrowsmith two-node search interface: A tutorial on finding meaningful links between two disparate sets of articles in medline. *Comput Methods Prog Biomed* 2009;94(2):190–7.
- [16] Ahlers CB, Hristovski D, Kilicoglu H, Rindflesch TC. Using the literature-based discovery paradigm to investigate drug mechanisms. *AMIA Annu Symp Proc* 2007;:6–10.
- [17] Hristovski D, Friedman C, Rindflesch TC, Peterlin B. Exploiting semantic relations for literature-based discovery. *Annual Symposium proceedings AMIA Symposium* 2006;:349–53.
- [18] Hu X, Li G, Yoo I, Zhang X, Xu X. A semantic-based approach for mining undiscovered public knowledge from biomedical literature. In: *Granular Computing*. 2005, p. 22–7.
- [19] Wilkowski B, Fiszman M, Miller CM, Hristovski D, Arabandi S, Rosemblat G, et al. Graph-based methods for discovery browsing with semantic predications. *AMIA Annu Symp Proc* 2011;.
- [20] Ramakrishnan C, Milnor WH, Perry M, Sheth AP. Discovering informative connection subgraphs in multi-relational graphs. *SIGKDD Explorations* 2005;7(2):56–63.
- [21] Goodwin JC, Cohen T, Rindflesch TC. Discovery by scent: Discovery browsing system based on the information foraging theory. In: *BIBM Workshops*. 2012, p. 232–9.
- [22] Miller CM, Rindflesch TC, Fiszman M, Hristovski D, Shin D, Rosemblat G, et al. A closed literature-based discovery technique finds a mechanistic link between hypogonadism and diminished sleep quality in aging men. *Sleep* 2012;35(2):279–85.
- [23] van der Eijk CC, van Mulligen EM, Kors JA, Mons B, van den Berg J. Constructing an associative concept space for literature-based discovery. *J Am Soc Inf Sci Technol* 2004;55(5):436–44.
- [24] Spangler S, Wilkins AD, Bachman BJ, Nagarajan M, Dayaram T, Haas P, et al. Automated hypothesis generation based on mining scientific literature. In: *Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. KDD ’14; New York, NY, USA: ACM. ISBN 978-1-4503-2956-9; 2014, p. 1877–86.
- [25] Zhang H, Fiszman M, Shin D, Wilkowski B, Rindflesch TC. Clustering cliques for graph-based summarization of the biomedical research literature. *BMC Bioinformatics* 2013;14:182.
- [26] Zhang H, Fiszman M, Shin D, Miller CM, Rosemblat G, Rindflesch TC. Degree centrality for semantic abstraction summarization of therapeutic studies. *Journal of Biomedical Informatics* 2011;44(5):830–8.
- [27] Cameron D, Bodenreider O, Yalamanchili H, Danh T, Vallabhaneni S, Thirunarayan K, et al. A graph-based recovery and decomposition of swanson’s hypothesis using semantic predications. *Journal of Biomedical Informatics* 2013;46(2):238–51.
- [28] Cairelli MJ, Miller CM, Fiszman M, Workman TE, Rindflesch TC. Semantic medline for discovery browsing: Using semantic predications and the literature-based discovery paradigm to elucidate a mechanism for the obesity paradox. In: *AMIA*. 2013, p. 164–73.
- [29] Swanson DR. Fish oil, raynaud’s syndrome, and undiscovered public knowledge. *Perspect Biol Med* 1986;30(1):7–18.
- [30] Swanson DR. Migraine and magnesium: eleven neglected connections. *Perspect Biol Med* 1988;31(4):526–57.
- [31] Swanson DR. Somatomedin c and arginine: implicit connections between mutually isolated literatures. *Perspectives in biology and medicine* 1990;33(2):157–86.
- [32] Smalheiser NR, Swanson DR. Indomethacin and Alzheimer’s disease. *Neurology* 1996;46(2).
- [33] Smalheiser NR, Swanson DR. Linking estrogen to alzheimer’s disease: An informatics approach. *Neurology* 1996;47(3):809–10.
- [34] Smalheiser NR, Swanson DR. Calcium-independent phospholipase a2 and schizophrenia. *Arch Gen Psychiatry* 1998;55(8):752–3.
- [35] Kilicoglu H, Shin D, Fiszman M, Rosemblat G, Rindflesch TC. Semmeddb: a pubmed-scale repository of biomedical semantic predications. *Bioinformatics* 2012;28(23):3158–60.
- [36] Wikipedia . <http://en.wikipedia.org/wiki/reachability>. 2012.
- [37] Blake C, Pratt W. Automatically identifying candidate treatments from existing medical literature. *AAAI Spring Symposium on Mining Answers from Texts and Knowledge Bases* 2002;.
- [38] Abhyankar S, Leishear K, Callaghan FM, Demner-Fushman D, McDonald CJ. Lower short- and long-term mortality associated with overweight and obesity in a large cohort study of adult intensive care unit patients. *Crit Care* 2012;16(6):R235.
- [39] Yetisgen-Yildiz M, Pratt W. A new evaluation methodology for literature-based discovery systems. *Journal of Biomedical Informatics* 2009;42(4):633–43.